



#### www.lemo.com

# **SUMMARY**

#### # Wires

**Series** 

 Low
 0

 High
 0

 Coax
 1

 Triax
 0

Quad 0
Fiber 0
Fluidic 0

Termination type Coupler/adapter/bridge

00

IP rating 50

**Cable Ø** 0.00 - 0.00 mm

Matching parts xxx



#### **Download**

Request a quote

Catalog

# **TECHNICAL DETAILS**

### **Mechanics**

Shell Style/Model ABF\*: Adapter from LEMO plug to BNC receptacle

Keying Circular (can rotate)

Housing Material Brass (nickel plated) shell, collet nut, latch sleeve and mid pieces

Cable Fixing p 0 - 0 mm

Variant

#### **Performance**

**Configuration** 0.25 : 1 Coax (50 Ohm)

Insulator T: PTFE Rated Current 4 Amps

## **Specifications**

Contact Type: Coaxial 50 Ohm

Max. Matings: 500

Contact Dia.: 0.7 mm (0.03in) Vtest: 2100 V (AC), 3000 V (DC)

Impedance: 50 Ohm VSWR: 1.09 + 0.11 \* f/GHz


## **Others**

Endurance (Shell): 5000 mating cycles

F ret (min): 100 N IP Rating: 50

# **DRAWINGS**

## **Draws**



#### **Dimensions**

	А	L	М	Weight
mm.	11.5	36	28	8.3
in.	0,45	1,42	1,10	0,33

# **RECOMMENDED BY LEMO**

**Tools** 

None

**Cables**