


Date	SYM	REVISION RECORD	AUTH	DR.	CK.
7/16/10	C	REDRAWN AND UPDATED MATERIAL NOTES	T.B.	B.S.	
8/31/12	D	ADDED DIM. Ø3.00 AND Ø4.30	T.B.	B.S.	
12/02/16	E	UPDATED TO ROHS 2 COMPLIANT	T.B.	B.S.	

NOTES:

1. MATERIAL:

HOUSING : POLYPROPYLENE
 FLAMMABILITY RATING: UL94 HB, UL FILE NO. E216959
 TEMPERATURE RANGE: -10°C TO +100°C
 RIVETS: BRASS, NICKEL PLATED.
 SPRING: SPRING STEEL, NICKEL PLATED.
 CONTACT RESISTANCE: UNDER 50m Ω FOR ± CONTACTS PER EIA-540J000
 ROHS 2 COMPLIANT

Tolerance (Except as noted)	 Memory Protection Devices, Inc 200 Broad Hollow Road, Farmingdale, New York 11735		
	decimal ±.5 (.020)	Scale	Drawn By B.S. Approved By T.B.
Fractional ± .8 (.030)	Title THREE "AA" CELL HOLDER		
Angular ± 3°	Date 12/02/16	Drawing Number BC3AAW	