| Date     | SYM | REVISION RECORD                | AUTH | DR.  | CK. |
|----------|-----|--------------------------------|------|------|-----|
| 11/19/05 | А   | ADDED "ROHS COMPLIANT"         | T.B. | B.S. |     |
| 10/14/06 | В   | ADDED UL FILE NO.              | T.B. | B.S. |     |
| 11/21/14 | С   | UPDATED TO ROHS 2<br>COMPLIANT | Т.В. | B.S. |     |
|          |     |                                |      |      |     |
|          |     |                                |      |      |     |



## NOTES:

MATERIAL: PET, 0.25mm (0.010") THICK, WHITE UL FILE #E93687 FLAMMABILITY RATING: VTM-2 ROHS 2 COMPLIANT

| Tolerance<br>(Except as noted) | <b>MPD</b> Mem                                     | ory Protection Devices, Inc |                |                  |  |  |  |
|--------------------------------|--|-----------------------------|----------------|------------------|--|--|--|
| (lixcept us noted)             | 200 Broad Hollow Road, Farmingdale, New York 11735 |                             |                |                  |  |  |  |
| decimal                        |  |                             | Scale          | Drawn By B.S.    |  |  |  |
| ±.5 (.020)                     |  |                             |                | Approved By T.B. |  |  |  |
| Fractional                     | Title<br>BATTERY INSULATOR                         |                             |                |                  |  |  |  |
| ± .8 (.030)                    |  |                             |                |                  |  |  |  |
| Angular                        | Angular Date                                       |                             | Drawing Number |                  |  |  |  |
| ± 3°                           | 11/21/14 BI-UM-3-4                                 |                             |                | JM-3-4           |  |  |  |