

Arc Flash Labeling Solutions

Panduit Arc Flash Labeling Solutions are designed to comply with the latest regulations including the 2015 NFPA 70E Standard, also called Electrical Safety in the Workplace. Panduit solutions provide comprehensive identification of hazardous energy throughout the infrastructure to protect employees and equipment. Labels are available in pre-printed, print-on-demand, and custom printed versions for flexibility in indoor and outdoor applications.



New Standards and Requirements

Standards 2015 NFPA 70E 2014 NEC 2012 CSA Z462 4.3.5.4 Requirements 130.5 (D) - Equipment Labeling. 110.16 Arc-Flash Hazard Warning. "Equipment Labeling. Electrical Electrical equipment such as switchboards, panel Electrical equipment, such as switchgear, equipment* shall be field marked boards, industrial control panels, meter socket panel boards, industrial control panels, with a label containing all the enclosures, and motor control centers that are in other meter socket enclosures, and motor control following information. than dwelling units and are likely to require examination, centers, that are in other than dwelling (a) at least one of the following: adjustment, servicing, or maintenance while energized units, and are likely to require examination, (i) available incident energy adjustment, servicing, or maintenance while energized, shall be field or factory shall be field-marked with a label containing all the and the corresponding following information: working distance; 1. Nominal system voltage marked to warn qualified persons of (ii) minimum arc-rating of PPE; (iii) required level of PPE; or 2. Arc flash boundary potential electric arc flash hazards. The 3. At least one of the following: marking shall meet the requirements in (iv) highest hazard/risk category a. Available incident energy and the 110.21(B) and shall be located so as to be for the equipment; corresponding working distance, or the arc flash PPE category in Table 130.7(C)(15)(A) (b) or Table 130.7(C)(15)(B) for the clearly visible to qualified persons before (b) nominal system voltage; (c) arc flash boundary: and examination, adjustment, servicing, or maintenance of the equipment. (d) date of the hazard analysis. equipment, but not both b. Minimum arc rating of clothing The method of calculating and data c. Site-specific level of PPE to support the information for the label shall be documented. Labels Exception: Labels applied prior to September 30, 2011, applied prior to the effective date are acceptable if they contain the available incident of this edition of this Standard are energy or required level of PPE. The method of acceptable if they contain the available incident energy or calculating and the data to support the information for the label shall be documented. required level of PPE." NFPA 70E 130.7 (E) (1) - Safety Signs and Tags Safety signs, safety symbols, or accident prevention tags shall be used where necessary to warn employees about electrical hazards that might endanger them.

Benefits **Kev Features Complies with the latest** Mitigates the risk of fines and accidents by increasing workplace visual communication NFPA standards and meets **OSHA** requirements** **Personal Protective** Provide quick visual identification of needed PPE along with required technical information in one label to aid in compliance with the NFPA 70E standards **Equipment (PPE) listing** and pictogram labels **Bilingual label** Two languages on one label; English and Spanish or English and French to ensure employee safety in a multiple language environment formats available **Raised Panel Labels** Crisp, clear, and durable legends; ideal for extended use in harsh environments **Complete system for arc flash** Allows user the ease and flexibility to create and print the desired labels on-demand labeling includes software. printers, and labels Highly visible colors and headers Provide employees the highest degree of safety through proper identification and communication with universal hazard symbols

displaying critical information

^{*}Electrical equipment, such as switchboards, panel boards, industrial motor control panels, meter socket enclosures, and motor control centers, that are in other than dwelling occupancies, and are likely to require examination, adjustment, servicing, or maintenance while energized.

^{** 2015} NFPA 70E and 2014 NEC.

NEC Warning Labels

NEC Warning Labels aid in compliance with Article 110.16 of the National Electric Code by providing clearly visible hazard information to warn qualified persons of potential electric arc flash hazards.



Basic



Standard

		Std. Pkg.	Std. Ctn.
Part Number	Part Description	Qty.	Qty.
Basic			
PPS0204W2100	4.50" x 2.25" (114.3mm x 57.2mm), black/orange, adhesive polyester sign, "WARNING". Potential Arc Flash Hazard.	5	100
PPS0204W2100-F	4.50" x 2.25" (114.3mm x 57.2mm), black/orange, adhesive polyester sign, "WARNING". Potential Arc Flash Hazard, written in French.	5	100
PPS0305W2100	3.50" x 5.00" (88.9mm x 127.0mm), black/orange, adhesive polyester sign, "WARNING". Potential Arc Flash Hazard.	5	50
PPS0507W2100	5.00" x 7.00" (127.0mm x 177.8mm), black/orange, adhesive polyester sign, "WARNING". Potential Arc Flash Hazard.	5	50
PPS0507W2100-F	5.00" x 7.00" (127.0mm x 177.8mm), black/orange, adhesive polyester sign, "WARNING". Potential Arc Flash Hazard, written in French.	5	50
Standard			
PVS0305W2102Y	3.50" x 5.00" (88.9mm x 127.0mm), WARNING (Header) orange and black, adhesive vinyl sign, "WARNING". ARC Flash and Shock Hazard.	5	50
PVS0305W2102Y-S	3.50" x 5.00" (88.9mm x 127.0mm), WARNING (Header) orange and black, adhesive vinyl sign, "WARNING". ARC Flash and Shock Hazard. Written in Spanish.	5	50
PVS0305W2102Y-F	3.50" x 5.00" (88.9mm x 127.0mm), WARNING (Header) orange and black, adhesive vinyl sign, "WARNING". ARC Flash and Shock Hazard. Written in French.	5	50

NFPA 70E Arc Flash Labels

NFPA 70E Arc Flash Labels provide all the detailed information needed for compliance with the 2015 NFPA 70E standard. These labels are available with WARNING or DANGER headers, universal hazard symbols and clear, concise, hazard descriptions. Labels are constructed of vinyl material (PVS) that accepts handwritten hazard information by using Panduit permanent black marking pens (PFX-0).





Detailed





Compact

	RNING
	Shock Hazard PPE Required
ARC FLASH PROTECTION As Flash Flash States (Integery Incident Energy (Integery Integer) Integer (Integer) Integer (Integ	SHOCK PROTECTION Weige from Heart United Agreem Boundary Peril Life Agreem Boundary Fred Life Agreem Boundary (Alex Class
Arco el	RTENCIA ectrico y
Adecuado Equip	carga eléctrica so de Protección PE) requerido
Profesción a Arco Dáctrico Colomia Palayo a Arco Mario Songla Instante Songla Instante di Mario de Arco Mario Lance de Inspec Lance de Inspec	Protección a Ejectrocución Pulgo si Charange Santos Aconsissos Limitade Aconsissos Bernadas Burnadas Proteinio
Equipment Et	Determine the manual states and the states are states as the states are states are states as the states are states are states as the states are

Detailed Bilingual

Part Number	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty
Detailed			
PVS0305W2103Y	3.50" x 5.00" (88.9mm x 127.0mm), WARNING (Header) orange and black, adhesive vinyl sign, "WARNING". Potential Arc Flash and Shock Hazard with detailed write-on area.	5	100
PVS0305W2110-F	3.50" x 5.00" (88.9mm x 127.0mm), WARNING (Header) orange and black, adhesive vinyl sign, "WARNING". Electrically Interlocked Handle, written in French.	5	50
PVS0305D2101Y	3.50" x 5.00" (88.9mm x 127.0mm), DANGER (Header) red and white, adhesive vinyl sign, "DANGER". Potential Arc Flash Exists with detailed write-on area.	5	50
PVS0507W2103Y	5.00" x 7.00" (127.0mm x 177.8mm), WARNING (Header) orange and black, adhesive vinyl sign, "WARNING". Potential Arc Flash and Shock Hazard with detailed write-on area.	5	100
PVS0507D2101Y	5.00" x 7.00" (127.0mm x 177.8mm), DANGER (Header) red and white, adhesive vinyl sign, "DANGER". Potential Arc Flash Exists with detailed write-on area.	5	50
PVS0305W2101Y-F	5.00" x 7.00" (127.0mm x 177.8mm), DANGER (Header) red and white, adhesive vinyl sign, "DANGER". Potential Arc Flash Exists with detailed write-on area. Written in French.	5	50
PVS0305W2103-F	5.00" x 7.00" (127.0mm x 177.8mm), DANGER (Header) red and white, adhesive vinyl sign, "DANGER". Potential Arc Flash Exists with detailed write-on area. Written in French.	5	100
PVS0507W2101Y-F	5.00" x 7.00" (127.0mm x 177.8mm), DANGER (Header) red and white, adhesive vinyl sign, "DANGER". Potential Arc Flash Exists with detailed write-on area. Written in French.	5	50
Compact			
PVS0204W2103Y	2.25" x 4.50" (57.2mm x 114.3mm), WARNING (Header) orange and black, adhesive vinyl sign, "WARNING". Potential Arc Flash and Shock Hazard with detailed write-on area.	5	100
PVS0204D2101Y	2.25" x 4.50" (57.2mm x 114.3mm), DANGER (Header) red and white, adhesive vinyl sign, "DANGER". Potential Arc Flash Exists with detailed write-on area.	5	100
Detailed Bilingual			
PVS0705W2105Y-S	7.00" x 5.00" (177.8mm x 127.0mm), WARNING (Header) orange and black, adhesive vinyl sign, "WARNING". Arc Flash and Shock Hazard, with detailed write-on area. Written in English and Spanish.	5	100
PVS0705D2105Y-S	7.00" x 5.00" (177.8mm x 127.0mm), DANGER (Header) red and white, adhesive vinyl sign, "DANGER". Arc Flash and Shock Hazard, with detailed write-on area. Written in English and Spanish.	5	100
PVS0705W2105Y-F	7.00" x 5.00" (177.8mm x 127.0mm), WARNING (Header) orange and black, adhesive vinyl sign, "WARNING". Arc Flash and Shock Hazard, with detailed write-on area. Written in English and French.	5	100
PVS0705D2105Y-F	7.00" x 5.00" (177.8mm x 127.0mm), DANGER (Header) red and white, adhesive vinyl sign, "DANGER". Arc Flash and Shock Hazard, with detailed write-on area. Written in English and French.	5	100

Arc Flash Labels with (PPE) Pictograms and Listings

Arc flash labels with detailed PPE information that is compliant with the 2015 NFPA 70E standard. These labels provide a helpful guide for employees to select PPE appropriate to the electrical hazard. PPE information is customized based on the specific hazard risk category. Labels are constructed of vinyl material (PVS) that accepts handwritten hazard information by using Panduit permanent black marking pens (PFX-0).



Detailed with PPE Pictograms



Detailed with PPE Listing

Part Number	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty.
Detailed with PPE Pic	etograms		
PVS0507W2104Y-0	PPE Pictograms for Hazard Risk Category 0.	5	100
PVS0507W2104Y-1	PPE Pictograms for Hazard Risk Category 1.	5	100
PVS0507W2104Y-2	PPE Pictograms for Hazard Risk Category 2.	5	100
PVS0507W2104Y-3	PPE Pictograms for Hazard Risk Category 3.	5	100
PVS0507W2104Y-4	PPE Pictograms for Hazard Risk Category 4.	5	100
Detailed with PPE Lis	ting		
PVS0507W2106Y-0	PPE Listing for Hazard Risk Category 0.	5	100
PVS0507W2106Y-1	PPE Listing for Hazard Risk Category 1.	5	100
PVS0507W2106Y-2	PPE Listing for Hazard Risk Category 2.	5	100
PVS0507W2106Y-3	PPE Listing for Hazard Risk Category 3.	5	100
PVS0507W2106Y-4	PPE Listing for Hazard Risk Category 4.	5	100

Arc Flash Print On-Demand Labels

Panduit offers a variety of durable polyester label options for use with the TDP43ME Printer to create customized Arc Flash labels. If additional protection is desired for printed Arc Flash labels due to harsh environments or UV fading, clear overlaminate sheets (T200X000YK1, T225X000YK1, T400X000YK1, and T425X000YK1) are also available.



		Std. Pkg.	Std. Ctn.
Part Number	Part Description	Qty.	Qty.
C200X400A51	2.00" x 4.00" (50.8mm x 101.6mm), polyester safety label, WARNING (Header) orange and black, 250 labels per roll.	1	4
C200X400YZ1	2.00" x 4.00" (50.8mm x 101.6mm), polyester safety label, DANGER (Header) red and white, 250 labels per roll.	1	4
C400X400A51	4.00" x 4.00" (101.6mm x 101.6mm), polyester safety label, WARNING (Header) orange and black, 250 labels per roll.	1	4
C400X400YZ1	4.00" x 4.00" (101.6mm x 101.6mm), polyester safety label, DANGER (Header) red and white, 250 labels per roll.	1	4
C400X600A51	4.00" x 6.00" (101.6mm x 152.4mm), polyester safety label, WARNING (Header) orange and black, 100 labels per roll.	1	4
C400X600YX1	4.00" x 6.00" (101.6mm x 152.4mm), polyester arc flash label, orange header, 100 labels per roll.	1	4
C400X600YZ1	4.00" x 6.00" (101.6mm x 152.4mm), polyester safety label, DANGER (Header) red and white,100 labels per roll.	1	4
Arc Flash Print On-D	emand Continuous Tape		
T400X000A91	4.00" x 50.00' (101.6mm x 15.2m), polyester arc flash tape, red header.	1	4
T400X000YX1	4.00" x 50.00' (101.6mm x 15.2m), polyester arc flash tape, orange header.	1	4

TDP43ME Thermal Transfer Desktop Printer



The TDP43ME desktop printer, designed to work with Panduit labeling software and media, quickly creates high-quality printed identification for Industrial Automation, Network Infrastructure, OEM, MRO, and Construction applications. This easy to set-up and operate printer, produces crisp, clear, durable printed legends on wire and cable markers, terminal block labels, conduit and voltage markers, control panel labels, patch panel labels, safety signs, pipe markers and arc flash labels.

Part Number	Part Description	Std. Pkg. Qty.
TDP43ME	300 dpi printer; includes printer, Panduit® Easy-Mark™ Labeling Software, RMEH4BL hybrid black ribbon, AC power adapter with US power cord, USB cable, user manual, quick start card, and driver disk.	1

Easy-Mark Labeling Software

Easy-Mark™ Labeling Software simplifies label creation for the specific needs of your applications. Intuitive interview process allows automatic generation of arc flash labels as well as other signs and markers. Software selects and formats the optimum label for your specific project. WYSIWYG (What You See Is What You Get) user interface, alpha/numeric serialization, data import, symbol import.



Part Number	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty.
PROG-EMCD3	Easy-Mark™ Labeling Software, CD-ROM.	1	10
PROG-EM2GO	Easy-Mark™ Portable Application, USB Flash Drive.	1	10

Arc Flash Labeling Applications Using TDP43ME and Easy-Mark™ Labeling Software



Detailed arc flash template from Easy-Mark™ Labeling Software using C400X600A51 label.

▲ WARN	ING	
ARC FLASH & SHOCK HAZARD APPROPRIATE PPE REQUIRED		
Arc Flash Hazard Category	2	
Incident Energy @ 18 inches	7 ca/clm²	
Arc Flash Boundary	55 inches	
Voltage Shock Hazard	480 VAC	
	42 inches	
Limited Approach Boundary		
	12 inches	
Limited Approach Boundary	12 inches	
Limited Approach Boundary Restricted Approach Boundary		

Compact and Logo arc flash template from Easy-Mark™ Labeling Software using C400X400A51 label.



Compact arc flash template from Easy-Mark™ Labeling Software using C400X400YZ1 label.



Detailed Bilingual arc flash template from Easy-Mark™ Labeling Software using C400X600YX1 label.

Custom Printed Arc Flash Labels


If your application demands custom printed information for your arc flash labeling, Panduit offers many options of custom printed arc flash labels. Fill out the custom arc flash label order form with your specific values, information, and even a company logo, and Panduit will create and print the specified label. Look for the icon below at www.panduit.com/safety to download electronic copies of the Custom Arc Flash Label order form.



WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT CANADA Markham, Ontario cs-cdn@panduit.com Phone: 800.777.3300 PANDUIT EUROPE LTD. London, UK cs-emea@panduit.com Phone: 44.20.8601.7200 PANDUIT SINGAPORE PTE. LTD. Republic of Singapore cs-ap@panduit.com Phone: 65.6305.7575 PANDUIT JAPAN Tokyo, Japan cs-japan@panduit.com Phone: 81.3.6863.6000 PANDUIT LATIN AMERICA Guadalajara, Mexico cs-la@panduit.com Phone: 52.33.3777.6000 PANDUIT AUSTRALIA PTY. LTD. Victoria, Australia cs-aus@panduit.com Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to www.panduit.com/warranty



Contact Customer Service by email: cs@panduit.com or by phone: 800.777.3300

©2016 Panduit Corp.
ALL RIGHTS RESERVED.
Printed in the U.S.A.
Product Bulletin Number IDCB61--SA-ENG
replaces SA-IDCB53
2/2016

