AR EYE PROTECTION 120000 KLEIN TOOLS KLEIN TOOLS KLEIN TOOLS, US

Strippers, Cutters and Crimpers

Manufactured with the needs of the professional tool user in mind, Klein strippers, cutters, and crimpers are designed to get jobs done with precision and quality.

For Professionals... Since 1857™



Wire Strippers/Cutters

Additional Features:

- Easy-to-read markings
- Precision shear-type blades
- Cleanly shears 6-32 and 8-32 screws
- Cat. No. 11054GLW features glow in the dark grips to easily locate your tool in dark or low lit areas



Glow in the Dark Grips

11054GLW

Cat. No.	Handle Color	Overall Length	Strips and Cuts	Screw Shearing	Weight
11053	Blue/Red	7-1/8" (181.0 mm)	6 - 12 AWG Stranded (10 mm² - 2.5 mm²)	6-32 and 8-32	5.4 oz. (153 g)
11054	Blue/White	7-1/8" (181.0 mm)	8 - 16 AWG Solid (8.4 mm ² - 1.3 mm ²), 10 - 18 AWG Stranded (5.3 mm ² - 0.82 mm ²)	6-32 and 8-32	5.4 oz. (153 g)
11054GLW	Glow	7-1/8" (181.0 mm)	8 - 16 AWG Solid (8.4 mm ² - 1.3 mm ²), 10 - 18 AWG Stranded (5.3 mm ² - 0.82 mm ²)	6-32 and 8-32	5.4 oz. (153 g)
11055	Blue/Yellow	7-1/8" (181.0 mm)	10 - 18 AWG Solid (4.0 mm ² - 0.75 mm ²), 12 - 20 AWG Stranded (2.5 mm ² - 0.50 mm ²)	6-32 and 8-32	5.4 oz. (153 g)
11057	Blue/Red	7-1/8" (181.0 mm)	20 - 30 AWG Solid (0.50 mm ² - 0.14 mm ²), 22 - 32 AWG Stranded (0.34 mm ² - 0.05 mm ²)	6-32 and 8-32	5.1 oz. (145 g)

Dual NM Cable Stripper/Cutter

Additional Features:

- 12/2, and 14/2 stripping slots quickly remove outer jacket of Type NM-B nonmetallic-sheathed cable
- Stripping holes easily remove insulation on 12 and 14 AWG sold wire
- Precision shear-type blades for square, clean cuts on solid copper wire
- Narrow nose fits into tight places



Cat. No.	Handle Color	Overall Length	Strips and Cuts	Туре	Screw Shearing	Weight
K1412	Yellow/White	7-3/4" (196.9 mm)	12 and 14 AWG Solid (2.5 mm ² and 1.5 mm ²)	NM-B Cable 12/2 and 14/2	6-32 & 8-32	6.6 oz. (187 g)

See page 310 for additional information on warnings.



Klein-Kurve[™] Wire Strippers/Cutters

Dual NMD-90 Cable Stripper/Cutter

Additional Features:

- Quickly removes outer jacket of Canadian NMD-90 Romex[®] Cable
- Strips, cuts, and loops 12 & 14 AWG solid wires
- Strips, cuts, and loops 14 & 16 AWG stranded wires
- Cleanly shears 6-32 and 8-32 screws



Romex® is a registered trademark of Southwire Company.

Cat. No.	Handle Color	Overall Length	Strips and Cuts	Туре	Screw Shearing	Weight
K1412CAN	Yellow/White	7-3/4" (196.9 mm)	12 and 14 AWG Solid (2.5 mm ² and 1.5 mm ²), 14 and 16 AWG Stranded (1.5 mm ² and 1.0 mm ²)	NMD-90 Cable 12/2 & 14/2	6-32 & 8-32	6.6 oz. (187 g)



Wire Strippers/Cutters

Additional Features:

- Compact, lightweight wire-stripping and cutting tools
- Narrow nose fits into tight places
- Hardened steel with precision ground stripping holes
- Do NOT use for cutting steel wire or screws



Cat. No.	Handle Color	Overall Length	Strips and Cuts	Weight
11045	Yellow	6-1/4" (158.8 mm)	10 - 18 AWG Solid (4.0 mm ² - 0.75 mm ²)	4.3 oz. (122 g)
11046	Red	6-1/4" (158.8 mm)	16 - 26 AWG Stranded (1.0 mm ² - 0.14 mm ²)	4.3 oz. (122 g)
11047	Yellow	6-1/4" (158.8 mm)	22 - 30 AWG Solid (0.34 mm ² - 0.05 mm ²)	4.3 oz. (122 g)
11049	Red	6-1/4" (158.8 mm)	8 - 16 AWG Stranded (6 mm ² - 1.0 mm ²)	4.3 oz. (122 g)

See page 310 for additional information on warnings.





Strippers, Cutters and Crimpers

Wire Strippers/Cutters

Dual-Wire Stripper/Cutter

Additional Features:

- Strips two wires in a single motion
- Paired stripping holes for 14 and 12 AWG solid wire
- One stripping hole for 10 AWG solid wire
- Shear-type cutting blades for square, clean cuts
- Narrow nose fits into tight places
- Hardened steel with precision ground stripping holes
- Do not use for cutting steel wire or screws

	SOLID TOLEZ IMANUE		KLEIN TOOLI	
S	W	/eight		11048

Gal. NU.		Overall Lellylli	ourips and outs	weigin
11048	Yellow	6-1/4" (158.8 mm)	10, 12, 14 AWG Solid (4.0 mm ² , 2.5 mm ² , 1.5 mm ²)	4.3 oz. (122 g)

Wire Strippers/Cutters

- Strips six standard wire sizes without nicking wire
- Scissors action of 1/2" (13 mm) wide cutter makes clean cuts with little effort
- Serrated nose jaws to bend, shape or pull wire; holes for looping wire ends
- Spring-loaded for self-opening action
- Comfortable, plastic-covered handles

SOLID 10-20 AWG	
STRANDED 12-22 AWG	

Cat. No.	Handle Color	Overall Length	Strips and Cuts	Weight
1011M	Blue	6-1/8" (155.6 mm)	0.15 to 4.0 mm ² Stranded Wire	3.7 oz. (104 g)
1011	Blue	6-1/8" (155.6 mm)	10 - 20 AWG Solid (4.0 mm² - 0.50 mm²), 12 - 22 AWG stranded (2.5 mm² - 0.34 mm²)	3.7 oz. (104 g)

Adjustable Wire Strippers/Cutters -Solid and Stranded Wire

- A handy, light, compact tool for stripping insulation
- Convenient hole for looping or bending wire
- Black-oxide finish with plastic-dipped handles
- Cuts, strips, and loops 12-26 solid and stranded wire
- Adjustable slide stop with set screw for repeat stripping work

Cat. No.	Handle Color	Overall Length	Strips and Cuts	Hold-Open Spring	Weight
1004	Yellow	5" (127.0 mm)	12 - 26 AWG Solid and Stranded (2.5 mm ² - 0.14 mm ²)	Yes	Yes
1003	Yellow	5" (127.0 mm)	12 - 26 AWG Solid and Stranded (2.5 mm ² - 0.14 mm ²)	No	2.2 oz. (64 g)

Adjustable Wire Stripper/Cutter -Solid and Stranded Wire

- Simply dial desired wire size for fast, easy stripping
- Adjustable tool makes short work of cutting and stripping operations
- Finely honed nose cutter easily gets into tight areas
- Wire gauge dial sets stripping dies to proper size, helps prevent nicked wire
- Black-oxide finish with plastic-dipped handles
- Spring-loaded design tool opens automatically after each action

ns SOLD 12-24 AWG STRANDED 12-24 AWG	-0	
	Weight	
Stranded (2.5 mm ² - 0.25 mm ²)	2 4 oz (68 g)	

Cat. No. Handle (olor Overall Length	Strips and Cuts	Weight
4007 Yellow	5-1/8" (130.2 mm)	12 - 24 AWG Solid and Stranded (2.5 mm ² - 0.25 mm ²)	2.4 oz. (68 g)

See page 310 for additional information on warnings



1004

www.kleintools.com



Wire Strippers/Cutters

Katapult[™] Wire Stripper/Cutters KATAPULT[®]

- Quick and easy wire stripping and cutting
- Compound action wire stripping: grip and strip via single action squeezing motion
- Precision machined stripping holes easily remove jacket insulation without damaging the wire
- Removes up to 1" (24 mm) in length of the insulation layer (jacket layer) in a single step
- Tension loaded wire-grip gently holds the cable in place while retaining the cable geometry
- Recoil spring design returns tool to ready position upon cycle completion
- Cast alloy chassis with heavy-duty Ecoat finish for corrosion resistance and durability
- Additional precision machined steel cutting blades available

Cat. No.	Handle Color	Overall Length	Strips	Weight
11063W	Blue/Black	6-19/32" (167.5 mm)	8 - 24 AWG solid (6.0 mm² - 0.34 mm²), 10-22 AWG stranded (6.0 mm² - 0.34 mm²)	12.0 oz. (340 g)



11063W

Cat. No.	Application	Weight			
Replacement Blades Sets					
VDV110-046	RG6 Coaxial Cable	0.16 oz. (4.5 g)			
11082	10 AWG Max Wire	0.16 oz. (4.5 g)			
11073	8 - 22 AWG ((6.0 mm ² - 0.34 mm ²)	0.01 lbs. (0.005 kg)			
11074 16 - 26 AWG ((1.0 mm ² - 0.14 mm ²)		0.01 lbs. (0.005 kg)			
Wire Stop/Gauge					
11081	Adjustable Wire Stop	0.16 oz. (4.5 g)			

Self-Adjusting Wire Stripper/Cutter

- Strips 10-20 AWG solid, 12-22 AWG stranded, and 12/2 & 14/2 Romex® wire
- Adjustable stopper to control the length of the core strip
- Convenient wire cutter in handle
- Grooved grips are designed for added comfort



Cat. No.	Handle Color	Overall Length	Strips and Cuts	Weight
11061	Blue/Black	8-1/4" (209.6 mm)	10 - 20 AWG Solid (4.0 mm ² - 0.50 mm ²), 12 - 22 AWG stranded (2.5 mm ² - 0.34 mm ²), 12/2 and 14/2 Romex [®]	12.6 oz. (358 g)

Romex® is a registered trademark of Southwire Company.

NM Cable Ripper

- Easy-to-use cable ripper
- Slit the outer jacket of Romex[®] cable (all sizes) and other nonmetallic (type NM) sheathed cable
- Measure conductor wire gauge

Cat. No.	Overall Length	Slits	Measures Wire Gauge	Weight
74017	4" (101.6 mm)	All Sizes of Romex [®] and NM	8 - 14 AWG (6 mm ² - 1 mm ²)	1.3 oz. (37 g)
Dama . @ !a				

Romex® is a registered trademark of Southwire Company.





35

11061



Combination Wire-Stripping and Crimping Tools

Multi-Pur	pose 6-i	in-1 Tool			1. DI	KLED	TOOLS, 771-
 Cleanly shears 	s bolts			~	~0		
 Easily cuts an 	-			6.	1 年少 駅		
Measures stud							and the second second
 Gauges wire s Crimps insula 			c0l				1000
 Comfortable, j 		d handles	500 8 - 22	AWG 10 - 26 AWG			
Cat. No. Hand	dle Color 🛛 O	verall Length Strips an	d Cuts		Bolt	Size	Weight
1000 Red	7-	3/4" (196.9 mm) 8 - 22 AW	G Solid (6.0 mm² - 0.34 mm²), 10) - 26 AWG Stranded (4.	0 mm ² - 1.0 mm ²) 4-40	, 6-32, 8-32, 10-24, 10-32	2 7.0 oz. (198 g)
Multi-Pur	pose El	ectrician's Tool			a han	St a KLEI	N TOOLS, TTT-
		the other halfway back ne utility of this tool	ear		~ (9 11)		
	rimping dies t	for 10-22 AWG insulated a	ind				
 Cleanly shears 	s bolts						1001
📍 Pivot nut adju	sts tension		00				
• Wire-looping	•		<u>50</u> 8-22	AWG STRANDED	(🍖) (🍖		
Full-sized, plas	stic-covered c	cushioned handles for com	nfort				
Cat. No. Han	dle Color 🛛 O	verall Length Strips an	d Cuts		Bolt	Size	Weight
1001 Red	8-	1/2" (215.9 mm) 8 - 22 AW	G Solid (6.0 mm² - 0.34 mm²), 10) - 26 AWG Stranded (4.	0 mm ² - 1.0 mm ²) 4-40	, 6-32, 8-32, 10-24, 10-32	2 7.5 oz. (213 g)
Multi-Pur	nnse I n	ng-Nose Tool					TOOLS, STI-
	-				0. 1.18	A CONTRACTOR	2
 Easily cuts an Narrow, serra 		e to pull, loop, and bend v	vire				
 Narrow, serra Long, curved 	-		VIIC		and a dist.	H	
	0	front of the pivot for max	imum ease-of-use in reach	ing into tight places			
 Crimps insula 	ted and non-i	nsulated terminals and 7 t	o 8 mm ignition terminals				1010
Cleanly shears			cul				
 Plastic-covere 	d cushioned l	handles for comfort	00 10 - 2	12 - 22 AWG			
	landle Color	Overall Length	Strips and Cuts	Bolt Size		Connectors	Weight
1010 B	lue	8-1/4" (209.6 mm)	10 - 20 AWG, 12 - 22 AWG	4-40, 5-40, 6	-32, 8-32, 10-32, 10-24	10 - 22 Gauge	6.9 oz. (196 g)
Cnimnin	a Tool	0					
Crimpin	IY IUUI	2					
Crimping	/Cutting	Tools -					
		sulated Termin	als	1			
 Crimping die 	marked for in:	sulated and non-insulated		e~7 ((学)	1	
solderless ter	minals and co	onnectors					
		orking in confined spaces					1005
 Specially hard Hot riveted in 			bblo				
- not-rivered jo	IIIL IUI SIIIUOTI	n action and no handle wo	มมเต				
Cat. No.	Overa	ll Length Ha	Indle Finish Ha	ndle Color	Crimps	V	/eight

Cat. No.	Overall Length	Handle Finish	Handle Color	Crimps	Weight	
1005	9-3/4" (247.7 mm)	Plastic-dipped	Red	10 - 22 AWG (4.0 mm ² - 0.34 mm ²)	12.8 oz. (363 g)	
Journeyman Series – Dual-material handles						
J1005	9-3/4" (247.7 mm)	Journeyman	Red/Black	10 - 22 AWG (4.0 mm ² - 0.34 mm ²)	13.4 oz. (381 g)	

See page 310 for additional information on warnings.





Crimping Tools

Crimping/Cutting Tool - Non-Insulated Terminals

- Designed for crimping non-insulated solderless terminals and connectors
- Specially hardened wire cutter in nose
- Tapered nose for working in confined spaces
- Hot-riveted joint for smooth action and no handle wobble



Cat. No.	Handle Color	Overall Length	Crimps	Weight
1006	Black	9-3/4" (247.7 mm)	10 - 22 AWG (4.0 mm² - 0.34 mm²)	13.6 oz. (386 g)

10%

Large Crimp Tool - Compound-Action

- Crimps #6-4/0 AWG battery lugs and terminals
- Ultra-comfortable hand grips for easy use
- All-in-one, integral crimp nest. No removable parts or rotating dies
- High-leverage handles and compound-action mechanism for superior mechanical advantage
- Adjustment screw allows user to control crimp depth

Cat. No.	Handle Color	Overall Length	Crimps	Weight
2006	Red	19-1/2" (495.3 mm)	#6 - 4/0 AWG battery lugs and terminals	3.8 lbs. (1.72 kg)

Ratcheting Crimpers

Ratcheting Crimpers - Insulated Terminals

- Cat. No. T1715 full cycle ratcheting crimper crimps insulated terminals in wire sizes 22-16 (front cavity), 16-14 (middle cavity), and 12-10 (rear cavity)
- Cat. No. T1710 compound-action tool crimps 10-22 AWG insulated terminals to meet or exceed MIL-SPEC pull-out tests
- Cat. No. T1710 features special locator to quickly position terminal to double crimp
- Built-in ratchet with safety release assures uniform crimps every time
- Compound lever-action of narrow span handles puts more crimping power into each squeeze
- Comfort-grip plastic handles



Cat. No.	Handle Color	Overall Length	Crimps	Weight
T1715	Black	9" (228.6 mm)	22-16/16-14/ 12-10	1.1 lbs. (0.50 kg)
T1710	Black	9" (228.6 mm)	10 - 22 AWG	1.1 lbs. (0.50 kg)

See page 310 for additional information on warnings.



2006