Flora Wearable GPS

Created by Becky Stern



Last updated on 2016-10-10 07:53:34 PM UTC

Guide Contents

Guide Contents	2
Overview	3
Hook up GPS	5
Program FLORA	7
Basic Echo Test	7
Install Adafruit GPS Library	7
Load Echo Demo	8
Getting location data	10
Detailed GPS Test	10
Downloads	13
Files	13
Downloads:	13
Schematic & Fabrication Print	13

Overview



This module is the best way to add a GPS to your wearable project. It's part of the Adafruit Flora series of wearable electronics, designed specifically for use with the Flora motherboard. Installed on the PCB is the latest of our Ultimate GPS modules, a small, super-thin, low power GPS module with built in data-logging capability! This module's easy to use, but extremely powerful:

- -165 dBm sensitivity, 10 Hz updates, 66 channels
- Designed for wearable use with the Flora system
- Only 20mA current draw
- RTC battery-compatible sew a battery on to create a atomic-precision real time clock
- Built-in datalogging
- >25Km altitude
- Internal patch antenna + u.FL connector for external active antenna

• Fix status LED

This guide will get you started with the Flora GPS.

Hook up GPS



Use alligator clips to connect Flora's 3.3V pad to the 3.3V pad on the GPS. Likewise connect RX to TX and TX to RX, then finally GND to GND.

Unlike the GPS breakout and GPS shield we carry, the Flora GPS is for use with 3.3V power and logic only!



The four connectors are all in a row just to the left of Flora's JST battery connector for easy sewing. But test your project with alligator clips before sewing it in!

Program FLORA



Make sure the USB cable is connecting your computer and Flora.

Basic Echo Test

We'll start with the most basic test, where we listen to the raw GPS data, to make sure it shows up! Copy and paste this code into a new sketch window and upload it to your Flora

Install Adafruit GPS Library

Our helper library will make using the GPS easy since we have working code already.<u>The</u> <u>library is available on GitHub</u> (http://adafru.it/nCR)

You can download the most recent version by clicking here to grab a Zip file with the library files:

Download Adafruit_GPS

http://adafru.it/oLE

Uncompress the zip and find the folder named Adafruit_GPS and check that the Adafruit_GPS folder contains Adafruit_GPS.cpp and Adafruit_GPS.h

Place the **Adafruit_GPS** library folder your **arduinosketchfolder**/libraries/ folder. You may need to create the **libraries** subfolder if its your first library. Restart the IDE.

We also have a great tutorial on Arduino library installation at: http://learn.adafruit.com/adafruit-all-about-arduino-libraries-install-use

Restart the Arduino IDE

Load Echo Demo

We'll begin by loading up the HardwareSerial echo test example available in the Adafruit_GPS library

ile	Edit Sketch	Tools Help			
	New Open Open Recent Sketchbook	Ctrl+N Ctrl+O	PS	Using Hardware Serial (e.g.	GPS Flora or FeatherWing)
	Examples			A	ing. Best used with
	Save	Ctrl+W Ctrl+S		Adafruit FRAM I2C Adafruit GPS Library	blank
		Ctrl+Shift+S		Adafruit HDC1000 Library Adafruit HMC5883 Unified	due_parsing due_shield_sdlog
	Page Setup Print	Ctrl+Shift+P Ctrl+P		Adafruit HX8357 Library Adafruit IL19340	echo flora_dumplog
	Preferences	Ctrl+Comma		Adafruit INA219 Adafruit IO Arduino	flora_gpslog
1	-	Ctrl+Q		Adafruit LED Backpack Library Adafruit LIS3DH Adafruit MAX31855 library	GPS_HardwareSerial_EchoTes GPS_HardwareSerial_Parsing leo_echo

Wire up the GPS module according to the hookup.<u>Check your board and serial port</u> <u>settings</u> (http://adafru.it/aRS) and upload this sketch to your Flora using the Upload button in the IDE. Open up the **Serial Monitor.** You should see something like the following from the serial monitor. You may not have as many numbers, but there should be sentences that start with **\$GPRMC** and **\$GPGGA**, etc. If you see text like that it means your GPS and connection are working fine.

COM6	
	Send
•••••••••••••••••••••••••••••••••••••••	//////////////////////////////////////
\$GPVTG,0.00,T,,M,0.03,N,0.06,K,A*38	
\$PGTOP,11,3*6F	
\$GPGGA,224424.000,4043.5460,N,07400.2854,W,1,7,1.11,14	15.8,M,-34.2,M,,*62
\$GPGSA,A,3,09,15,05,26,08,29,21,,,,,1.40,1.11,0.85*07	1
\$GPRMC,224424.000,A,4043.5460,N,07400.2854,W,0.12,0.00),081112,,,A*7E
\$GPVTG,0.00,T,,M,0.12,N,0.23,K,A*3F	
\$PGTOP,11,3*6F	
\$GPGGA,224425.000,4043.5459,N,07400.2854,W,1,7,1.11,14	15.8,M,-34.2,M,,*69
\$GPGSA, A, 3, 09, 15, 05, 26, 08, 29, 21, , , , , , 1.40, 1.11, 0.85*07	7
\$GPGSV,2,1,08,15,83,168,33,26,53,052,48,21,50,307,22,2	29,33,218,33*79
\$GPGSV, 2, 2, 08, 05, 31, 075, 30, 09, 16, 159, 33, 08, 13, 040, 38, 4	11,,,*44
\$GPRMC, 224425.000, A, 4043.5459, N, 07400.2854, W, 0.05, 0.00	0,081112,,,A*73
\$GPVTG,0.00,T,,M,0.05,N,0.10,K,A*39	
\$PGTOP, 11, 3*6F	
\$GPGGA,224426.000,4043.5460,N,07400.2854,W,1,7,1.11,14	5.8.M34.2.M*60
\$GPGSA, A, 3, 09, 15, 05, 26, 08, 29, 21, ,, ,, 1.40, 1.11, 0.85*07	
\$GPRMC, 224426.000, A, 4043.5460, N, 07400.2854, W, 0.07, 0.00	
\$GPVIG,0.00,T,,M,0.07,N,0.12,K,A*39	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
egrv16,0.00,1,,m,0.07,M,0.12,K,K"35	
Autoscroll	No line ending 🚽 57600 baud

Getting location data

Detailed GPS Test

Now that we know it basically works, we'll try to get 'fix data' from the GPS. For this, you will have to have the GPS outside. It cannot be inside a building, even if its right at the window. The silver antenna must be pointing up with a clear view of the sky!

ile Edit Sketch	Tools Help			
New Open Open Recer Sketchbook	1	25 Heing Hardware Serial		
Examples		Adafruit FRAM I2C	•	
Close	Ctrl+W	Adafruit GPS Library		blank
Save Save As	Ctrl+S Ctrl+Shift+S	Adafruit HDC1000 Library Adafruit HMC5883 Unified	1	due_parsing due_shield_sdlog
Page Setup Print	Ctrl+Shift+P Ctrl+P	Adafruit HX8357 Library Adafruit IL19340 Adafruit INA219		echo flora_dumplog flora_gpslog
Preferences	Ctrl+Comma	Adafruit IO Arduino		GPS_HardwareSerial_EchoTest
Quit	Ctrl+Q	Adafruit LED Backpack Library	•	GPS_HardwareSerial_Parsing
	support open s	Adafruit LIS3DH Adafruit MAX31855 library	1	leo_echo leo_locus_dumpbasic

Wire up the GPS module according to the hookup



<u>Check your board and serial port settings (http://adafru.it/aRS)</u> and upload this sketch to your Flora using the Upload button in the IDE.

Place the GPS module (still connected to the Flora) outside. Once the GPS has located the satellite data, the red LED on the GPS will stop blinking.

If you see the LED blinking once a second, it does not yet have a fix!

It can take many minutes to get a fix if it doesn't see any satellites immediately.

Once it has a fix, you can check the serial monitor for the GPS data, which includes the current date and time in UTC. It will also give you your latitude, longitude and approximate altitude with the Serial monitor

GPS modules will always send data EVEN IF THEY DO NOT HAVE A FIX! In order to get 'valid' (not-blank) data you must have the GPS module directly outside, with the square ceramic antenna pointing up with a clear sky view. In ideal conditions, the module can get a fix in under 45 seconds. however depending on your location, satellite configuration, solar flares, tall buildings nearby, RF noise, etc it may take up to half an hour (or more) to get a fix! This does not mean your GPS module is broken, the GPS module will always work as fast as it can to get a fix.

COM6		۲.
	Send	
\$PGTOP, 11, 3*6F		*
\$GPGGA,225356.000,4043.5720,N,07400.2788,W,1,7,1.05,60.4,M,-34.2,M,,*57		
\$GPRMC, 225356.000, A, 4043.5720, N, 07400.2788, W, 0.42, 81.93, 081112, , , A*42		
\$PGTOP,11,3*6F		=
\$GPGGA,225357.000,4043.5720,N,07400.2786,W,1,7,1.05,60.4,M,-34.2,M,,*58		
\$GPRMC, 225357.000, A, 4043.5720, N, 07400.2786, W, 0.39, 81.93, 081112, , , A*41		
Time: 22:53:56.984		
Date: 8/11/2012		
Fix: 1 quality: 1		
Location: 4043.5717N, 7400.2783W		
Speed (knots): 0.39		
Angle: 81.93		
Altitude: 60.40		
Satellites: 7		
\$PGTOP, 11, 3*6F		
\$GPGGA,225358.000,4043.5719,N,07400.2785,W,1,7,1.05,60.4,M,-34.2,M,,*5E		
\$GPRMC, 225358.000, A, 4043.5719, N, 07400.2785, W, 0.34, 81.93, 081112, , , A*4A		-
Autoscroll No line ending	57600 baud	•

Now we know where we are. According to the GPS, my location is **4043.5715 N** (Latitude 40 degrees, 43.5815 minutes North) & **07400.2783 W**. (Longitude 74 degrees, 0.2783 minutes West) To look at this location in Google maps, type **+40**° **43.5715'**, **-74**° **00.2783'** into the <u>google maps search box</u> (http://adafru.it/aMI) . Unfortunately gmaps requires you to use +/- instead of NSWE notation. N and E are positive, S and W are negative.

People often get confused because the GPS is working but is "5 miles off" - this is because they are not parsing the lat/long data correctly. Despite appearances, the geolocation data is NOT in decimal degrees. It is in degrees and minutes in the following format: Latitude: DDMM.MMMM (The first two characters are the degrees.) Longitude: DDDMM.MMMM (The first three characters are the degrees.)

Downloads

Files

- EagleCAD PCB files on GitHub (http://adafru.it/rPD)
- Fritzing object in the Adafruit Fritzing Library (http://adafru.it/aP3)

Downloads:

- <u>MTK3329/MTK3339 command set sheet</u> (http://adafru.it/qif) for changing the fix data rate, baud rate, sentence outputs, etc!
- Datasheet for the PA6H (MTK3339) GPS module itself used in version 3 of this module (http://adafru.it/ria)
- <u>MT3339 GPS PC Tool (windows only)</u> (http://adafru.it/rib) and the <u>PC Tool</u> <u>manual</u> (http://adafru.it/ric)
- Mini GPS tool (windows only) (http://adafru.it/rid)

Schematic & Fabrication Print



