



Metal thin film chip resistors (precision)

RR series

Features

- Precision chip resistors excellent in resistance tolerance, TCR, frequency performance, noise characteristics, and linearity.

Applications

- Consumer electronics that requires precision resistors
- All purpose resistors in any area of electronics


Part numbering system

Series code	RR 0816 P - 102 - D - (M) - (T5) - (***)			only given to 3 digit coders for RR0816 E-96 series
Size: RR0306, RR0510, RR0816, RR1220, RR1632, RR2632,				Taping quantity: RR1632, RR2632 5000pcs:T5 RR0306, RR0510, RR0816, RR1220: nocoder is given
Temperature coefficient of resistance				Letter M is added for RR1220 E-96 series 4digit codes
Nominal Resistance value	RR0306, RR0510, RR0816, RR1220	E-24: 3 digit, E-96: 4 digit		
	RR1632, RR2632: 4 digit		Resistance tolerance	

Electrical Specification

Type	Power ratings	Temperature coefficient of resistance (ppm/°C)	Resistance range(Ω) Resistance tolerance			Maximum voltage	Resistance value series	Operating temperature	Packaging quantity
			±0.1% (B)	±0.5% (D)	±1% (F)				
RR0306	1/20W	±25(P)	30≤R≤22k			15V	E-24, E-96	-55°C ~ 125°C	5,000pcs
		±100(R)	—	—	10≤R≤30				
RR0510	1/16W	±25(P)	100≤R≤100k			25V	E-24, E-96	-55°C ~ 125°C	10,000pcs
		±100(R)	—	—	10≤R≤91				
RR0816	1/16W	±25(P)	100≤R≤360k			75V	E-24, E-96	-55°C ~ 125°C	5,000pcs
		±50(Q)	—	—	10≤R≤91				
RR1220	1/10W	±25(P)	100≤R≤1M			100V	E-24, E-96	-55°C ~ 125°C	5,000pcs
		±50(Q)	—	—	10≤R≤91				
RR1632	1/8W	±5(V)	100≤R≤200k	—		150V	E-24, E-96	-55°C ~ 125°C	T5
		±10(N)		—					
		±25(P)	51≤R≤1M		—				
		±50(Q)	—	10≤R≤47		—			
RR2632	1/4W	±5(V)	100≤R≤200k	—		200V	E-24, E-96	-55°C ~ 125°C	T5
		±10(N)		—					
		±25(P)	51≤R≤1M		—				
		±50(Q)	—	10≤R≤47		—			

Dimensions



Type	Size (inch)	L	W	a	b	t
RR0306	0201	0.60±0.05	0.30±0.05	0.12±0.05	0.12±0.05	0.23±0.03
RR0510	0402	1.00±0.05	0.50±0.05	0.20±0.10	0.25±0.05	0.35±0.05
RR0816	0603	1.60±0.20	0.80±0.20	0.30±0.20	0.30±0.20	0.40±0.10
RR1220	0805	2.00±0.20	1.25±0.20	0.40±0.20	0.40±0.20	0.40±0.10
RR1632	1206	3.20±0.20	1.60±0.20	0.50±0.20	0.45±0.20	0.40±0.10
RR2632	1210	3.20±0.20	2.60±0.20	0.50±0.20	0.45±0.20	0.40±0.10

(unit : mm)